

## Technical Specifications

### RKHD-75F

**100 PSI                      460 V                      60 Hz                      3 Phase**

#### GENERAL DATA

Nominal Working Pressure	<b>100 psi</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
Maximum Ambient Temperature	<b>113 °F</b>	
Minimum Ambient Temperature	<b>41 °F</b>	

#### WORKING DATA

ACFM Max	<b>335 cfm</b>	
Total Package Max Current Draw at Full Load	<b>50 kW</b>	<b>105 A</b>
Total Power at No Load	<b>16 kW</b>	
Max Rotor Speed	<b>5000 rpm</b>	
Noise Level	<b>70 ± 3 dB</b>	

#### MAIN MOTOR

Driving System (Electric)	<b>Star/Delta</b>	
Power Transmission	<b>Direct Drive</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
N° Poles	<b>2</b>	
Max Motor Speed	<b>3540 rpm</b>	
Service Class	<b>S1 95%</b>	
Efficiency	<b>IE3</b>	
Form Factor	<b>B35</b>	
Protection	<b>IP 55</b>	

#### COOLING SYSTEM

Fan Motor Power	<b>0.3 kW</b>
Fan Motor Speed	<b>2900 rpm</b>
Protection	<b>IP44 class</b>
Insulation Class	<b>F</b>
Cooling Air Flow	<b>4400 cfm</b>

#### LUBRICATION

Oil Quantity	<b>5 gallons</b>
Oil Type	<b>PneuTech PG46</b>
Residual Oil	<b>≤ 3 ppm</b>

#### MACHINE DIMENSIONS AND WEIGHT

W x D x H	<b>77 X 48 X 63 inches</b>
Weight	<b>2632 lbs</b>
Outlet Air Diameter	<b>Female NPT 1 1/2"</b>

## Technical Specifications

### RKHD-75F

**110 PSI                      460 V                      60 Hz                      3 Phase**

#### GENERAL DATA

Nominal Working Pressure	<b>110 psi</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
Maximum Ambient Temperature	<b>113 °F</b>	
Minimum Ambient Temperature	<b>41 °F</b>	

#### WORKING DATA

ACFM Max	<b>328 cfm</b>	
Total Package Max Current Draw at Full Load	<b>51 kW</b>	<b>105 A</b>
Total Power at No Load	<b>17 kW</b>	
Max Rotor Speed	<b>5000 rpm</b>	
Noise Level	<b>70 ± 3 dB</b>	

#### MAIN MOTOR

Driving System (Electric)	<b>Star/Delta</b>	
Power Transmission	<b>Direct Drive</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
N° Poles	<b>2</b>	
Max Motor Speed	<b>3540 rpm</b>	
Service Class	<b>S1 95%</b>	
Efficiency	<b>IE3</b>	
Form Factor	<b>B35</b>	
Protection	<b>IP 55</b>	

#### COOLING SYSTEM

Fan Motor Power	<b>0.3 kW</b>
Fan Motor Speed	<b>2900 rpm</b>
Protection	<b>IP44 class</b>
Insulation Class	<b>F</b>
Cooling Air Flow	<b>4400 cfm</b>

#### LUBRICATION

Oil Quantity	<b>5 gallons</b>
Oil Type	<b>PneuTech PG46</b>
Residual Oil	<b>≤ 3 ppm</b>

#### MACHINE DIMENSIONS AND WEIGHT

W x D x H	<b>77 X 48 X 63 inches</b>
Weight	<b>2632 lbs</b>
Outlet Air Diameter	<b>Female NPT 1 1/2"</b>

## Technical Specifications

### RKHD-75F

**125 PSI                      460 V                      60 Hz                      3 Phase**

#### GENERAL DATA

Nominal Working Pressure	<b>125 psi</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
Maximum Ambient Temperature	<b>113 °F</b>	
Minimum Ambient Temperature	<b>41 °F</b>	

#### WORKING DATA

ACFM Max	<b>307 cfm</b>	
Total Package Max Current Draw at Full Load	<b>52 kW</b>	<b>105 A</b>
Total Power at No Load	<b>20 kW</b>	
Max Rotor Speed	<b>5000 rpm</b>	
Noise Level	<b>70 ± 3 dB</b>	

#### MAIN MOTOR

Driving System (Electric)	<b>Star/Delta</b>	
Power Transmission	<b>Direct Drive</b>	
Nominal Motor Power	<b>55 kW</b>	<b>75 HP</b>
N° Poles	<b>2</b>	
Max Motor Speed	<b>3540 rpm</b>	
Service Class	<b>S1 95%</b>	
Efficiency	<b>IE3</b>	
Form Factor	<b>B35</b>	
Protection	<b>IP 55</b>	

#### COOLING SYSTEM

Fan Motor Power	<b>0.3 kW</b>
Fan Motor Speed	<b>2900 rpm</b>
Protection	<b>IP44 class</b>
Insulation Class	<b>F</b>
Cooling Air Flow	<b>4400 cfm</b>

#### LUBRICATION

Oil Quantity	<b>5 gallons</b>
Oil Type	<b>PneuTech PG46</b>
Residual Oil	<b>≤ 3 ppm</b>

#### MACHINE DIMENSIONS AND WEIGHT

W x D x H	<b>77 X 48 X 63 inches</b>
Weight	<b>2632 lbs</b>
Outlet Air Diameter	<b>Female NPT 1 1/2"</b>