Rotary Screw Compressors RK Vorrinble Speed Drive Series 15HP-75HP



Features & Benefits

RK Variable Speed Drive Series 15HP-75HP

Rotary Screw Compressors





Vented Electrical Cabinet

Vented for maximum cooling of the drive (conveniently accessed from the front of the machine)



Low RPM Airend Assembly

The oversized airend assembly allows for a low RPM design which provides reduced maintenance, cooler running conditions, and an extended life expectancy.



Oversized Air/Oil Cooler

Easy-to-access and oversized to allow for higher ambient operating temperature isolation when compressor is not in use.



Direct Drive Design

Direct drive eliminates gear-sets which increases efficiency and reduces noise and vibration levels



Spin-on Filtration

Spin-on air/oil separators and oil filtration allow for quick and effortless replacement



Condensate Trap

The standard condensate trap, located at the discharge of the air cooler removes bulk water. Includes electric solenoid drain valve quick and effortless replacement



Integrated Oil Sump Tank

The oil sump tank is integrated directly with the air end, filtration, thermal valve, and MPCV. This feature reduces hose

connections and lessens the chance for oil leakage, and provides a compact design.



TEFC motor (totally enclosed fan-cooled)

As standard, all RK-VSD units come packaged with a TEFC motor. This feature protects the motor against dirty environments which increases bearing life and the

overall longevity of the compressor maintenance on the complete machine, especially the air filter.



Integrated Dryer Option

Integrating the dryer into the compressor saves time, money, and floor space. All RK Fixed Speed 5-40 HP compressors are available with or without a dryer.

This dryer is unique because it has a single point condensate drain, digital dew point meter, and is easily serviced.




Oversized Air-Oil Separator Tank

The oversized air-oil separator tank and element allows for effective 3 stage separation, less than 3ppm oil carry over and less than

0.02 bar pressure drop. The highest air quality is assured with renowned Mann filtration.

Efficiency Load Comparison Graph




Variable Speed Drive Technology



Variable Frequency Inverter Unit

- Unlimited motor starts per hour
- No inrush current to overheat the motor
- Consistent Discharge Pressure
- Set a 'target' pressure rather than load/unload set-points. Consistent pressure means consistent production results.
- Soft Motor Starts
- As opposed to full voltage motor starts on most fixed speed machines, the VSD drive initiates slow motor starts, thus significantly lowering the demand on your electrical meter
- Up to 85% Turn-Down
- The VFD runs the machine between 15-100% capacity in order to meet current demand.
- Reduced Power Consumption
- Unlike a fixed speed machine, KW consumption stays on par with your compressed air demand, resulting in significant energy savings.



Electronic Controller

- Pressure Parameters
- Set target pressure to match your exact demand
- Current Duty Cycle
- Monitor the demand that production is putting on the compressor
- Maintenance Timers
- Track and set your maintenance schedule
- Alarm Conditions/Reset
- Past and current alarms are recorded, allowing for quick diagnosis
- Cooling Fan Control
- Controls the air/oil cooling fan based on actual oil temperature conditions. Fan cycles only when needed.
- Discharge Pressure
- Displays current air discharge pressure
- Oil Temperature
- Protects against overheating by allowing this critical temperature to be easily monitored
- Phase Monitor
- Prevents reverse rotation and protects against power loss damage

RK Variable Speed Drive Series 15HP-75HP Specifications

| | HP | kW | CFM | PSI | dBA | NPT | Voltage (3ph) | Dimensions (in) | Weight (lbs) |
|------------------|----|----|-----|-----|-----|--------|------------------|-----------------|-----------------|
| RK-15VSD-115B | 15 | 11 | 60 | 115 | 65 | 3/4" | 460 | 53x28x48 | 705 |
| RK-15VSD-115B-L | 15 | 11 | 60 | 115 | 65 | 3/4" | 200/230 | 53x28x48 | 705 |
| RK-20VSD-115B | 20 | 15 | 80 | 115 | 65 | 3/4" | 460 | 53x28x48 | 728 |
| RK-20VSD-115B-L | 20 | 15 | 80 | 115 | 65 | 3/4" | 200/230 | 53x28x48 | 728 |
| RK-25VSD-115B | 25 | 18 | 97 | 115 | 68 | 1-1/4" | 460 | 66x30x56 | 794 |
| RK-25VSD-115B-L | 25 | 18 | 97 | 115 | 68 | 1-1/4" | 200/230 | 66x30x56 | 794 |
| RK-30VSD-115B | 30 | 22 | 123 | 115 | 68 | 1-1/4" | 460 | 66x30x56 | 926 |
| RK-30VSD-115B-L | 30 | 22 | 123 | 115 | 68 | 1-1/4" | 200/230 | 66x30x56 | 926 |
| RK-40VSD-115B | 40 | 30 | 166 | 115 | 68 | 1-1/4" | 460 | 66x30x56 | 1168 |
| RK-40VSD-115B-L | 40 | 30 | 166 | 115 | 68 | 1-1/4" | 200/230 | 66x30x56 | 1168 |
| RK-50VSD-115B* | 50 | 37 | 217 | 115 | 68 | 1-1/2" | 460 | 81x39x71 | 2116 |
| RK-50VSD-115B-L* | 50 | 37 | 217 | 115 | 68 | 1-1/2" | 200/230 | 81x39x71 | 2116 |
| RK-60VSD-115B* | 60 | 45 | 260 | 115 | 68 | 1-1/2" | 460 | 81x39x71 | 2360 |
| RK-60VSD-115B-L* | 60 | 45 | 260 | 115 | 68 | 1-1/2" | 200/230 | 81x39x71 | 2360 |
| RK-75VSD-115B* | 75 | 55 | 340 | 115 | 68 | 1-1/2" | 460 | 81x39x71 | 2690 |

^{*}Includes Moisture Separator



- VFD Drive
- Significant Energy Savings
- Cycling Cooling Fan
- Energy Savings/Longer Life
- Low Sound Enclosure
- Quiet Operation
- Production Flexibility
- Removable Panels
- Reduced Service Downtime
- Minimal Hose Design
- Reduced Oil Leakage
- Compact Footprint
- Installation Flexibility

5 Year Pneu-Assure Warranty

Industry-Leading Peace-of-Mind

5 Year Warranty on Major Components

Airend

Oil Sump Tank

Electric Motor(s)

Air Cooler

Oil Cooler

VSD Unit

✓ 1 Year Warranty on the Entire Unit

Regular maintenance NOT included

✓ Guaranteed Support

From Your Certified Distributor

✓ Technical Expertise

Industry-leading knowledge & experience

Warranty subject to change based on region and distributor's agreement.

Why PneuTech?

You are the #1 priority when you partner with PneuTech.

Your goals are our goals - because your success is our success.

Your experience is superior when partnering with PneuTech because of quality products and personal service.

You want efficiency, reliability and versatility when sourcing compressed air equipment - that's what we strive for.



Other PneuTech Products



RK Fixed Speed Rotary Screw 5HP-50HP



RSP Fixed Speed Rotary Screw 75HP-450HP



FHO Inline Filtration



CSO Oil Water Separators



Ri Fixed & Variable Speed Rotary Screw 60HP-220HP



RSP Variable Speed Rotary Screw 75HP-450HP



RDA Refrigerated Air Dryers



NGO Nitrogen Generators

Our Mission Statement

Using our combined industry experience, we provide knowledge, support, and superior products to compressed air distributors across the globe.

We are committed to producing positive results through being trustworthy, ethical, and accessible.

We are founded in the beliefs that through working together we can continue to transform the industry, while rising to turn challenges into opportunities.



United States | Australia
United Kingdom | New Zealand

PneuTech USA 550 Albion Avenue Schaumburg, IL 60193 888.966.9007

www.pneutech.com